

## CLAIMS

What is claimed is:

1. A method comprising:  
receiving a web page definition having a slicing tree describing an arrangement of a plurality of blocks in the web page; and  
rendering the web page on a display screen according to the slicing tree.
2. A method as recited in claim 1 wherein the web page definition further includes block property data associated with one or more of the plurality of blocks.
3. A method as recited in claim 2 further comprising scaling one or more of the plurality of blocks according to a function of display screen size and the block property data.
4. A method as recited in claim 2 further comprising selecting a combination of the plurality of blocks to be adapted such that information fidelity is maximized according to the expression:

$$IF(P) = \sum_{B_i \in P} IMP_i \cdot IF_{B_i} ,$$

1           where  $IMP_i$  is a value representing importance of block  $B_i$ ,  $IF_{B_i}$  is a value  
2           representing information fidelity of block  $B_i$ , and  $IF(P)$  is the total information  
3           fidelity of the web page.

4  
5           5.       A method as recited in claim 2 wherein the block property data  
6           comprises:

7                   an importance field;  
8                   a minimal perceptible size field;  
9                   a minimal perceptible height field;  
10                  a minimal perceptible width field;  
11                  an adjustability field; and  
12                  an alternative field.

13  
14  
15  
16           6.       A method as recited in claim 5 further comprising determining a  
17           scaling number using a capacity based ratio algorithm.

18  
19  
20           7.       A method as recited in claim 1 further comprising summarizing one  
21           or more of the plurality of blocks.

22  
23           8.       A method as recited in claim 1 further comprising associating a  
24           scaling factor with one or more of the plurality of blocks.  
25

1  
2 9. A method as recited in claim 1 further comprising generating a  
3 binary tree having a plurality of nodes, wherein each node corresponds to a  
4 combination of the plurality of blocks.

5  
6 10. A method as recited in claim 9 further comprising maximizing  
7 information fidelity subject to:  
8

9 
$$\sum_{B_i \in P'} \text{size}(ALT_i) + \sum_{B_i \in P'} MPS_i \leq \text{Area} ,$$

10 where  $ALT_i$  is an adapted representation of block  $B_i$ ,  $\text{size}(ALT_i)$  is a  
11 function that returns the size of  $ALT_i$ ,  $MPS_i$  is a value representing a minimum  
12 perceptible size of block  $B_i$ , and Area is a value representing the size of the target  
13 area in which the web page is rendered.  
14

15  
16 11. A method as recited in claim 1 further comprising scaling one or  
17 more of the blocks to maximize information fidelity subject to a target area on the  
18 display screen.  
19  
20  
21  
22  
23  
24  
25

1           12.    A computer-readable medium having stored thereon computer-  
2 executable instruction for performing a method comprising:

3           generating a web page definition having block property data defining a  
4 minimum perceptible size of a plurality of blocks in the web page.

5  
6           13.    A computer-readable medium as recited in claim 12, the method  
7 further comprising generating a slicing tree defining the horizontal and vertical  
8 arrangement of the plurality of blocks in the web page.  
9

10  
11          14.    A computer-readable medium as recited in claim 12 wherein the  
12 block property data further comprises an importance value, an alternative  
13 representation, an adjustment value, a minimum perceptible height value, and a  
14 minimum perceptible width value.  
15

16  
17          15.    A computer-readable medium as recited in claim 12 wherein the web  
18 page definition is dynamically generated on a server side object.  
19

20  
21          16.    A computer-readable medium as recited in claim 12, the method  
22 further comprising adapting one of more of the blocks to fit in a target area based  
23 on the minimum perceptible size.  
24  
25

1  
2 17. A processor-readable medium having processor-executable  
3 instructions for performing a method comprising:  
4 receiving a web page definition defining a plurality of blocks in a web page;  
5 determining a maximum information fidelity associated with a combination  
6 of summarized and unsummarized blocks in the web page; and  
7 rendering the web page with the combination of summarized and  
8 unsummarized blocks.  
9

10  
11 18. A processor-readable medium as recited in claim 17, the method  
12 further comprising:  
13 scaling one or more of the blocks based on a slicing tree definition in the  
14 web page definition.  
15

16  
17 19. A processor-readable medium as recited in claim 17, wherein the  
18 determining a maximum information fidelity comprises:  
19 generating a binary tree having a plurality of nodes, each node representing  
20 a combination of unsummarized blocks; and  
21 performing a depth-first traversal of the binary tree to identify the  
22 combination of unsummarized blocks for which the information fidelity is  
23 maximized.  
24  
25

1  
2           20.    A processor-readable medium as recited in claim 19, wherein the  
3 performing a depth-first traversal comprises sorting the plurality of blocks in order  
4 of decreasing importance.  
5

6  
7           21.    A processor-readable medium as recited in claim 19, wherein the  
8 performing a depth-first traversal comprises determining whether the combinations  
9 of unsummarized blocks are valid.  
10

11           22.    A processor-readable medium as recited in claim 19, wherein the  
12 performing a depth-first traversal comprises determining whether the combinations  
13 of unsummarized blocks are feasible in accordance with block property data.  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25

1           23.    A system comprising:  
2           a browser operable to browse a web page based on a web page definition  
3 comprising a slicing tree defining an arrangement of a plurality of rectangular  
4 regions in the web page.

6           24.    A system as recited in claim 23, wherein the web page definition  
7 further comprises:  
8

9           parametric data associated with one of the plurality of rectangular regions,  
10 the parametric data describing adaptability parameters related to the associated  
11 rectangular region.

13           25.    A system as recited in claim 24 further comprising:  
14           a proxy module operable to generate an adapted web page definition based  
15 on the parametric data; and  
16           a rendering module operable to render an adapted web page based on the  
17 adapted web page definition.  
18

20           26.    A system as recited in claim 25, wherein the proxy module is further  
21 operable to determine a set of the plurality of rectangular regions to be summarized  
22 such that information fidelity of the adapted web page is maximized.  
23  
24  
25

27. A system as recited in claim 26, wherein the proxy module is further operable to traverse a binary tree having nodes representing sets of unsummarized rectangular regions.



1           28.    A method of generating a web page having a plurality of blocks, the  
2 method comprising:

3           determining a first information fidelity associated with a first set of the  
4 plurality of blocks;

5           determining a second information fidelity related to a second set of the  
6 plurality of blocks; and

7           rendering the first set of blocks in a summarized fashion if the first  
8 information fidelity is greater than the second information fidelity.  
9

10  
11          29.    A method as recited in claim 28 further comprising:  
12 arranging the plurality of blocks according to a slicing tree.  
13

14  
15          30.    A method as recited in claim 28 further comprising:  
16 scaling a first block based on a minimum perceptible size value associated  
17 with the first block and a target display area.  
18

19          31.    A method as recited in claim 28 further comprising associating an  
20 importance value to each block in the plurality of blocks.  
21

22  
23          32.    A method as recited in claim 31 wherein the importance values range  
24 from zero to one.  
25

1  
2 33. A method as recited in claim 29 wherein the slicing tree is defined in  
3 a markup language file defining the web page.  
4

5 34. A method as recited in claim 33 wherein the markup language file  
6 further comprises block property data for each of the plurality of blocks in the web  
7 page.  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25